

1

VIDEO SERVER

CROSS REFERENCE TO CO-PENDING APPLICATIONS

6 This application is related to commonly assigned and co-pending U.S. Patent Application
Serial No. 33012/263/101, filed _____, and entitled "Video on Demand Transaction
Server"; U.S. Patent Application Serial No. 33012/262/101, filed _____, and
entitled "Video On Demand System"; U.S. Patent Application Serial No. 33012/265/101
11 , filed _____, and entitled "Video on Demand Transaction Gateway"; and U.S. Patent
Application Serial No. 33012/266/101, filed _____, and entitled "A Web Based
Video on Demand Administration Application", all of which are incorporated by reference.

a

BACKGROUND OF THE INVENTION

16

1. **Field of the Invention:** The present invention generally relates to digital data transmission of
video information and more particularly to the delivery of user selected video information to
subscribing users.

21

2. **Description of the Prior Art:** The mass distribution of video programming signals (i.e.,
television) was originally accomplished primarily by the broadcasting of a very high frequency

1 (i.e., VHF) carrier containing an amplitude modulated video signal and a frequency modulated
audio signal. Through the addition of more broadcasting transmitters, a modest number of
different programming signals could be simultaneously distributed to a large number of potential
users with a modest capital commitment. Using this technique, the capital commitment increases
almost linearly with number of different programming channels within the limits of the available
6 spectrum space for separate and independent carriers.

Within a couple of decades, most of the scarce VHF spectrum space had been committed,
and increasing demand for additional programming channels resulted in the allocation of spectrum
space in the ultra-high frequency (i.e., UHF) region. Whereas virtually all receivers became UHF
compatible, as a matter of policy, and UHF channels were assigned to requesters, it was
11 appreciated that there were no economies of scale through the addition of more broadcast
programming channels.

The cable television channel era was the result, wherein a capital commitment was
required to wire each user home within a service area. As a result, about one hundred separate
programming channels became readily available at a lesser cost than providing the same number of
16 channels using conventional broadcast means. Initially, cable television was simply an analog
system in which low power modulated carriers were transferred over a coaxial cable rather than
being broadcast into the ether at substantially higher power levels. The cost saving was realized
because the broadcasting was accomplished at substantially lower power.

With approximately one hundred different programming channels, it is typical to charge
21 cable service user fees in accordance with a hierarchy of programming channels. The least
expensive channels tend to be the preexisting broadcast channels and those cable channels

1 supported primarily by advertisers which are intended for the most general audiences. The
subscriber fees to access other channels increase as the programming becomes more specialized,
advertising revenue becomes less likely to pay the programming costs, and the programming
materials tend to have substantial economic value through other distribution channels. The so-
called "premium channels" which show current and/or near current movies without advertising are
6 typical of the higher cost programming options.

Most commercial cable television providers package the various programming channels
into programming channel groups with different prices such that a given user can select a suitable
programming package and pay the equivalent fee. Typically, a cable provider box, which couples
the user television receiver to the coaxial cable source, is controlled by the cable television
11 provider to give access to a given user to only those channels for which the appropriate subscriber
fee has been paid.

The most expensive cable television channels currently available are "pay-per-view" or
PPV. With the PPV concept, a given user can subscribe to a given programming channel for a
single individual program of up to several hours for a separate subscriber fee. Typically, PPV
16 channels provide sporting events and almost current movies.

Perhaps the major disadvantage of the PPV concept as currently implemented, is that the
programming is provided in the "broadcast" mode. That means that the programming begins and
runs on a predefined schedule. As a result, programming is missed if the user receives a telephone
call, for example, during the viewing. Furthermore, it ordinarily requires the user to allocate
21 viewing time to coincide with the predefined schedule. To overcome this disadvantage, many
users rent video programs as video cassette recordings (i.e., VCR) from commercial stores which

1 provide such a rental service. This permits the viewer to watch the program in accordance with
her/his own schedule, stop the program during interruptions, and replay portions of the program
which may not be readily understood. The primary disadvantage of the VCR rental approach is
the need to physically go to the rental store to obtain the program and return to the rental store to
return the recording.

6 With the capital commitment for cable television in place, their appear to be substantial
new uses for the basic coaxial pathway. Such uses include, telephone, computer modem,
facsimile, and video conferencing. To properly coordinate such diverse information transmission
activities, attention is being directed to digital transmission schemes which provide for easier
management of the distribution resources. U.S. Patent No. 5,570,355, issued to Dail et al.,
11 discusses the handling of a number of diverse information transmissions within a single system.
U.S. Patent No. 5,673,265, issued to Gupta et al., U.S. Patent No. 5,754,773, issued to Ozden et
al., and U.S. Patent No. 5,799,017, issued to Gupta et al., all discuss multi-media distribution
systems. U.S. Patent No. 5,555,244, issued to Gupta et al., is directed to multimedia distribution
to residential users.

16 The digitization of video results in a great deal of data which must be transferred at a high
rate to yield acceptable performance and resolution. By current standards, 3mbits/sec. is
considered to be a very acceptable rate. Such high data rates require systems which can provide
high data rate transmission. U.S. Patent No. 5,724,543, issued to Ozden et al., U.S. Patent No.
5,699,362, issued to Makam, and U.S. Patent Nol. 5,826,110, issued to Ozden et al., all concern
21 themselves with high data rate retrieval and transmission. U.S. Patent No. 5,675,573, issued to
Karol et al., discusses the management of high data rate bandwidths.

1 In addition to retrieval and transmission of the required high data rates, there is also the
need to provide high speed switching for switching as between data sources and destinations.
U.S. Patent No. 5,751,704, issued to Kostic et al., and U.S. Patent No. 5,740,176, issued to
Gupta et al., discuss high speed digital switching systems.

6 Whether it is data storage and retrieval, data transmission, or data switching, the
fundamental technological problem associated with digital video results from the sheer volume of
digitized video data and the tremendous rate at which it must be provided to the ultimate user for
satisfactory performance. One technique for reduction of the volume problem is in reducing the
resolution (and hence the volume of data) for those applications for which such reduction is
acceptable. U.S. Patent No. 5,623,308 and U.S. Patent No. 5,691,768, both issued to Civanlar et
11 al., directly address the handling of multiple resolution digitized video signals within a single
system.

Notwithstanding attempts to reduce the resolutions to the lowest acceptable levels, the
total data volume of any commercially useful system will remain high. The most common way to
treat extremely high data volumes is through data compression. U.S. Patent No. 5,710,829,
16 issued to Chen et al., U.S. Patent No. 5,742,343, issued to Haskell et al., and U.S. Patent No.
5,619,256, issued to Haskell et al., are concerned with digital compression techniques. Specific
attention to compression of digitized video is found in U.S. Patent No. 5,764,803, issued to
Jacquin et al. Compression of 3-dimensional images is treated by U.S. Patent No. 5,612,735,
issued to Haskell et al.

21 The evolving techniques of digitized video transmission have resulted in a transmission
standard, called Asynchronous Transfer Mode (ATM). U.S. Patent No. 5,668,841, issued to

1 Haskell et al., describes data transmission using the ATM standard. An ATM converter is
discussed in U.S. Patent No. 5,809,022, issued to Byers et al. U.S. Patent No. 5,724,349, issued
to Cloonan et al., suggests an approach to packet switching within an ATM system. An ATM
architecture is discussed in U.S. Patent No. 5,781,320, issued to Byers. Interfacing to ATM
systems is addressed in U.S. Patent No. 5,842,111, issued to Byers.

6 A solution to the PPV problems noted above utilizing digitized video has been termed,
Video on Demand (or VOD). In a VOD system, digitized video programming is made available
to individual cable television subscribers in response to specific requests made by the user. U.S.
Patent No. 5,867,155, issued to Williams, describes the use of VOD for a very specialized
application. Sea Change, International, has proposed a VOD approach for cable television
11 subscribers. U.S. Patent No. 5,583,561, issued to Baker et al., assigned to the assignee of the
present invention and incorporated herein by reference, discloses and teaches a complete, modern
VOD system employing a centralized architecture utilizing an enterprise server developed by
Unisys Corporation.

SUMMARY OF THE INVENTION

The present invention overcomes many of the disadvantages found within the prior art by providing a video on demand system which separates the tasks of supplying video to subscribers from the tasks associated with managing the subscriber interface. The key to this approach is to provide an architecture in which the necessary functions are divided into two separate portions. A first hardware and software subsystem, called a video server, is specifically dedicated to retrieving and transmitting the stream of video information. Virtually no other functions are performed by the video server. A second hardware and software subsystem, called the transaction server, handles virtually all other functions including control interface with the subscribers, spooling of digitized video data, subscriber accounting, etc.

The video server has two primary design criteria. First, it must be highly optimized to handle the extremely high input/output data rates. In essence, this is the sole function of the video server, and therefore, the design of the video server hardware and software are most directed towards this characteristic. Because the role of the video subsystem is simplified and single dimensional, video subsystems utilizing current technology can be produced at a surprisingly low cost.

The second major design criterion of the video server subsystem involves modularity. The addition of active subscribers, each viewing individual video programs (or the same program at different times), tends to increase the total input/output load of the video server subsystem linearly. Therefore, there is great economic incentive to design the video server subsystem in such

1 a manner that the hardware resources to implement the video subsystem may be linearly increased
in relatively small (and inexpensive) increments.

In the preferred mode of the present invention, the video server subsystem consists of a
modularly expandable Unisys CMP memory platform. All video data is spooled into and streamed
out of the memory installed in this platform. One or more input/output data rate optimized,
6 industry compatible computers operating under a readily available, commercial operating system,
such as Windows NT provide the simple timing and control functions.. Using 3 mbits/second per
video stream as a standard, each such device can effective service thousands of different and
independent video streams. Within each video server, storage can be added to handle more video
programs and communication interfaces can be added to provide more video streams. Therefore,
11 the same design architecture and components are suitable for a wide range of system sizes, and
the incremental capital cost to the video programming supplier can be readily determined as
further subscribers are added to the system.

Unlike the video server subsystem which is optimized to provide a low cost, highly
modular approach to a single function, the transaction server is optimized to provide a low cost
16 approach to a wide and highly expandable variety of functions. In fact, all of the functions of the
video on demand system, except for the video streaming function performed by the video server,
are accomplished by the transaction server. Typical tasks include: transactional interface with the
subscribers, subscriber fee accounting, requested program spooling, video server subsystem
control, receiving video from a satellite and storing it in an archive, etc. Thus, the ideal
21 hardware/software platform for implementation of the transaction server is a readily expandable,
highly flexible, high availability, highly recoverable, realtime oriented mainframe system. In the

1 preferred mode of the present invention, the Unisys 2200 is used to host the transaction server.

In accordance with the present invention, a subscribing user transfers a programming request to the transaction server. The transaction server makes the required subscriber accounting entry and notifies the corresponding preloaded video server platform of the new subscriber request. If the asset is not preloaded, in addition to the subscriber accounting, the transaction server must access the request video program and spool it for storage in the video server. Depending upon the rate of use of the requested video program, the data might be stored in memory (for high volume use), on a disk or other mass storage device (for medium volume use), or in some other medium (for low volume use).

In the preferred mode of the present invention, the user is permitted to pause, reverse, or fast forward the requested video program through commands entered from the on-set subscriber box. These functions are intended to appear similar to normal VCR commands to the user. These commands are sent to the transaction server which utilizes them to control the corresponding video stream output of the video server subsystem. Thus the user is provided with all of the advantages of VCR rental without the need to physically transport the medium (i.e., cassette tape) back and forth between the rental store and the user site.

In view of the power and flexibility of the transaction server, other diverse but somewhat related functions may be provided. For example, a user might order a pizza delivery via the on-set subscriber box to transaction server interface, or the user might access the internet, e-mail, or faxes via the transaction server. If this interface is implemented over a readily available, publically accessible, network, such as the internet, many additional functions are possible.

BRIEF DESCRIPTION OF THE DRAWINGS

Other objects of the present invention and many of the attendant advantages of the present invention will be readily appreciated as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings, in which like reference numerals designate like parts throughout the figures thereof and wherein:

Fig. 1 is a schematic diagram showing the operation of the overall video on demand system of the present invention;

Fig. 2 is a schematic diagram showing spooling of the video programming data from typical mass storage devices;

Fig. 3 is a schematic diagram showing the generation of a video stream from spooled data within a memory subsystem;

Fig. 4 is a schematic diagram showing video streaming as synchronized on one minute boundaries;

Fig. 5 is a schematic diagram showing operation of a video server platform;

Fig. 6 is a schematic diagram showing video streaming of multiple programs from a single video server platform;

Fig. 7 is a schematic diagram showing video streaming from video programming data spooled on disk drive mass storage units;

Fig. 8 is a schematic diagram showing video streaming from video programming data stored on both disk drive mass storage units and memory subsystems;

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 is a schematic diagram 10 showing the overall video on demand system of the present invention. A subscribing user (not shown) is positioned adjacent standard television receiver 34. Through this television receiver, the user is capable of viewing video programming material transferred to his location via coaxial cable 30 from network 26 in the fashion currently known in the cable television industry. The interface between coaxial cable 30 and standard television receiver 34 is provided by subscriber box 32, which provides the conversion between MPEG-2 digitized video format and the analog video signal required by television receiver 34.

In many respects, subscriber box 32 is similar to the subscriber boxes utilized with existing cable television systems with the slight functional differences described in more detail below. The basic reason for these slight differences is to permit a subscribing user to communicate with transaction server 12 in a two directional manner. Not only does subscriber box 32 receive video programming data via coaxial cable 30 and present it to television receiver 34, but subscriber box 32 is capable of transferring user requests via coaxial cable 30 and network 26 to transaction server 12 via path 28. The most important requests in accordance with the present invention are those which initiate and control the individualized video on demand programming.

When the user is interested in viewing a particular video program, a request is made from subscriber box 32 and transferred to transaction server 12 via coaxial cable 30, network 26, and path 28. Transaction server 12, a Unisys 2200 server system in the preferred embodiment, is provided access to video programming information from satellite receiver 14, from analog video

1 storage 16 and digital mass storage 18. In each instance, the video programming data is either
received in digital form or converted to digital form. According to the preferred embodiment of
the present invention, the MPEG-2 standardized format is utilized.

Whenever a request is received, transaction server 12 checks various security parameters,
makes appropriate subscriber billing entries, and generally performs all of the necessary
6 administrative functions as described below in greater detail. Additionally, transaction server 12
spools digital video data for transmission by the video server assigned to the requesting
subscriber. One of video server platforms 20, 22, ..., or 24 is assigned the task by transaction
server 12 and the spooled digital video data is supplied via the digital data bus shown. In the
preferred mode of the present invention, each video server platform is a separate industry
11 compatible, Windows NT based, computer platform. Once downloaded to the selected video
server, the requested video programming is transmitted via network 26 and coaxial cable 30 to
subscriber box 32 and television receiver 34.

Fig. 2 is a schematic diagram showing the spooling of data from digital disk mass storage devices. For the preferred mode of the present invention, the digitized video programming data is stored in MPEG-2 format. In the spooling process, the MPEG-2 organized and placed into memory as a programming file 54. To produce commercially acceptable video, 3mbits/second is required. That means that a two hour video program requires the about 2.7 billion bytes of data storage. Because of cost considerations, many of the programs having low and moderate usage will best be stored on mass storage disk until requested

Individual storage disks 48, 50, ..., and 52 each store a number of video programs in MPEG-2 format. As requested, this data is transferred via storage bus 46 through disk control 42 through I/O bus 38 and placed in memory 55 via path 40. A software program spools the data to the ATM interface 54 at the required speed..

Fig. 3 is a schematic diagram showing spooling of high volume digitized video program.

For those programs having a high user demand, it is much more efficient to spool the program files from random access memory rather than mass storage disk systems. In this context, high volume means a high probability that the given program will be in use during high service volume periods. That means that there will need to be random access storage allocated to the storage of that given program during peak memory demand. As a result, the system should simply allocate random access storage to that given program. Very popular, recent movies are typical of such high volume programs.

If a program is a high volume program, it is preferably stored in auxiliary memory 56.

Upon request, software residing in memory 36 directs the spooling of data from auxiliary memory 56 and transferring it via path 40 and I/O bus 38 to ATM interface 54. It should be noted that this is significantly more efficient than the spooling operation shown in Fig. 2, since the video data only needs to be read out of memory instead of having to be loaded from disk each time the data is used. Furthermore, there is no additional cost if a program is of sufficiently high volume that the required random access memory must be allocated to the program anyway.

Fig. 4 is a schematic diagram 58 showing the synchronization of a given video program around one minute time slots. In concept, the present invention provides subscribers with video on demand. However, as a practical matter, by synchronizing multiple users around one minute time slots, the maximum number of transmissions to all users of the given video program cannot exceed 60 per hour of programming and 120 for a two hour standard video program. That means that for a given high volume program (which may be requested by hundreds or even thousands within the length of time to view the program) each requester is assigned to an appropriate time slot.

First time slot 60 provides the first minute of video programming to one or more requesters. During one minute time slot 62, the initial requesters receive the second minute of programming, and one or more requesters may be starting with the first minute of programming. At the nth time slot 64, the initial requesters are viewing the nth minute of programming, the second group of requesters is viewing the n-1 minute of programming, and the nth group of requesters is viewing the first minute of programming. At final time slot 66, the initial requesters are viewing the final minute of programming, the second group of requesters is viewing the second to last minute of programming, and a new group of requesters is viewing the initial minute of programming.

The reduction in total data requirements utilizing these one minute time slots is substantial. The total delay to a requester is no more than one minute and will average one half minute, making the process perfectly acceptable and barely noticeable to the subscribers.

Fig. 5 is a schematic diagram of a single industry compatible, Windows NT based video server platform. The video server subsystem is composed of a number of separate and largely independent video server platforms. Each is configured to have a maximum memory configuration and maximum I/O configuration. Digitized video programming data in the MPEG-2 format are spooled from transaction server 68 via interconnect 70 into the assigned video server platform. Program 74 and program 72 are shown. These programs are place onto network 78 under control of transmission control software 80 for transfer to the requesting subscriber(s). For a given program being sent to a single user, transmission control software 80 simply retrieves the video data from memory in a sequential fashion at 3 mbits/second and places it on network 78.

FIG. 5 is a schematic diagram of a single industry compatible, Windows NT based video server platform. The video server subsystem is composed of a number of separate and largely independent video server platforms. Each is configured to have a maximum memory configuration and maximum I/O configuration. Digitized video programming data in the MPEG-2 format are spooled from transaction server 68 via interconnect 70 into the assigned video server platform. Program 74 and program 72 are shown. These programs are place onto network 78 under control of transmission control software 80 for transfer to the requesting subscriber(s). For a given program being sent to a single user, transmission control software 80 simply retrieves the video data from memory in a sequential fashion at 3 mbits/second and places it on network 78.

Fig. 6 is a schematic diagram showing spooling of high volume program 82 into the video server platform of Fig. 5. The spooling is performed by the transaction server as discussed above. The spooled data is transferred to the video server platform via I/O bus 84. Up to ten programs can be stored and streamed from a single video server. For simplicity, only one video server is shown. For a view of multiple video servers within a system, refer to Fig. 1.. All other referenced elements are as previously described.

FIG. 6 is a schematic diagram showing spooling of high volume program 82 into the video server platform of Fig. 5. The spooling is performed by the transaction server as discussed above. The spooled data is transferred to the video server platform via I/O bus 84. Up to ten programs can be stored and streamed from a single video server. For simplicity, only one video server is shown. For a view of multiple video servers within a system, refer to Fig. 1.. All other referenced elements are as previously described.

Fig. 7 is a schematic diagram showing the spooling of low to moderate volume digitized video program data. For lower volume programs, storage on disk storage mass memory may be appropriate. A low volume video program is one in which it is highly unlikely that more than one request is received during the runtime of the video program. Therefore, the servicing of the request is most probably an index sequential task for retrieving the data and transmitting it to the user. This is readily distinguishable from the high volume video programs for which transmissions within multiple and perhaps many of the one minute time slots is expected (see also Fig. 4). These programs are spooled to the video server platform as shown. The remaining referenced elements are as previously described.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

57

Fig. 8 is a schematic diagram showing spooling of low and high volume video programs to the same video server platform. All referenced elements are as previously described.

FIG. 8 is a schematic diagram showing spooling of low and high volume video programs to the same video server platform. All referenced elements are as previously described.

Fig. 9 is a block diagram 84 of the maximum configuration of the transaction server of the preferred mode of the present invention. In this preferred mode, the video server is implemented using a current model Unisys mainframe system. In accordance with this product, the system is expandable from a single processor, single main memory, and single I/O controller to the maximum system shown.

Instruction processors 102, 104, 106, 108, 110, 112, 114, and 116 communicate with main memories 86, 88, 90, and 92 via crossbar interconnects 94, 96, 98, and 100. Each instruction processor may be coupled with up to four third-level caches, as shown. Direct Input/Output bridges 118, 120, 122, 124, 126, 128, 130, and 132 each handle video output functions. Each of the direct Input/Output bridges may be partitioned into separate partitions as shown. Additional description of partitioning may be found in U.S. Patent Application Serial No. 08/779,472, filed January 7, 1997, commonly assigned to the present invention and incorporated herein by reference.

Fig. 10 is a detailed functional diagram 134 of the transaction server. Communication with subscriber box 32 (see also Fig. 1) is managed by set top management module 142. Initial requests are selected by the user and honored through utilization of menu transaction module 140. After initiation of the servicing of a given request, control of the matter is given to session manager 138 for completion. Any and all communication with the transaction server are monitored by security module 148. Administration module 136 provides overall control of the transaction server.

The transaction server may be utilized to interface with the internet. The selected hardware and software system selected for the preferred mode provide internet server facilities in a commercially usable form. Video server session management module 146 provides the detailed functions (e.g., spooling of digital video programming) associated with the primary video on demand service. These control functions are directly interfaced to the video server subsystem via video server interface 150.

Event logging module 154 journals the functions performed. This log is made available to digital network control services 152. Media directory services and asset management module 162 provides long term control and asset management. Historical storage of these data is performed by asset storage management and asset capture.

In performing the actual video on demand service, the appropriate requested digitized video program is accessed from databases 160. It is spooled by asset delivery, video streaming module 158. The transfer is made via video server interface 156 (see also Fig. 1).

Fig. 11 is a detailed functional diagram 166 of the entire video on demand system. Disk tape storage 168 retains the basic programming data. As explained above, only the very lowest usage frequency assets will be stored in analog form. The transaction gateway 170 is preferably housed within a Unisys HMP/IX 4800 mainframe system.

6 A request for a particular video on demand program is initiated by the user (not shown) at set-top subscriber box 190. In the preferred mode, this request may be initiated by a wireless remote control in the manner known in the art and available from Scientific Atlanta or General Instruments. The request is transferred via the coaxial network or cable to quadrature amplitude modulation device 180, available from either General Instruments or Scientific Atlanta. The request is transferred to transaction gateway 170 via pathway 184.

11 The requested video on demand program is spooled from transaction gateway 170 to video on demand appliance 174 via messaging interface 172, if available in disk/tape storage 168. The requested video on demand program is streamed from video on demand appliance 174 via ATM network 176, as described in more detail below. Multiplexer 180 combines the video on demand programming with other programming sources (e.g., broadcast) and supplies this combination to quadrature amplitude modulation device 180 for transmission to the set-top subscriber box 190 and television receiver 186.

Fig. 12 is a detailed functional diagram of the operation of video on demand appliance, VODA, 174 (i.e., video server). Requested video programming is transferred to VODA 174 in MPEG-2 format via path 172. Preferably, VODA 174 contains Unisys CMP memory platform 192 into which the digitized video data is spooled. The data is placed serially into memory such that program 194 is a memory storage area having a complete digital program stored in sequential order. Programs 196, 198, and 200 are spooled into memory in a similar fashion.

Intel processors 204, 206, 208, 210, 212, and 214 all have access to Unisys CM:P memory platform 192 as shown. In the preferred mode, these processors operate under Windows NT and stream each of the video programs from Unisys CMP memory platform 192 to the user via path 176 (see also Fig. 11). Streaming involves the timed access from memory of the serially stored program which produces the desired resolution in time and space. The preferred mode of the present invention is modularly expandable to stream thousands of separate video on demand programs.

1. The first part of the paper is devoted to a review of the literature on the effects of the 1997-1998 Asian financial crisis on the economies of the Asian countries. The second part of the paper is devoted to a review of the literature on the effects of the 1997-1998 Asian financial crisis on the economies of the Asian countries. The third part of the paper is devoted to a review of the literature on the effects of the 1997-1998 Asian financial crisis on the economies of the Asian countries. The fourth part of the paper is devoted to a review of the literature on the effects of the 1997-1998 Asian financial crisis on the economies of the Asian countries. The fifth part of the paper is devoted to a review of the literature on the effects of the 1997-1998 Asian financial crisis on the economies of the Asian countries. The sixth part of the paper is devoted to a review of the literature on the effects of the 1997-1998 Asian financial crisis on the economies of the Asian countries. The seventh part of the paper is devoted to a review of the literature on the effects of the 1997-1998 Asian financial crisis on the economies of the Asian countries. The eighth part of the paper is devoted to a review of the literature on the effects of the 1997-1998 Asian financial crisis on the economies of the Asian countries. The ninth part of the paper is devoted to a review of the literature on the effects of the 1997-1998 Asian financial crisis on the economies of the Asian countries. The tenth part of the paper is devoted to a review of the literature on the effects of the 1997-1998 Asian financial crisis on the economies of the Asian countries.